

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

Astral pH Minus Liquid

Version: 1

Revision date: 11/01/2017

Page 1 of 9

Print date: 11/01/2017

SECTION 1: IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Astral pH Minus Liquid
Chemical Name: sulphuric acid
Index No: 016-020-00-8
CAS No: 7664-93-9
EC No: 231-639-5
Registration No: 01-2119458838-20-XXXX

1.2 Relevant identified uses of the substance and uses advised against.

pH regulator

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **FLUIDRA COMMERCIAL, S.A.U.**
Address: Avda. Francesc Macià, 60, 20^a planta
City: 08208 Sabadell
Province: (Barcelona) Spain
Telephone: Tel: +34 93 724 39 00
Fax: Fax: +34 93 724 29 93
E-mail: fds@inquire.com
Web: www.astralpool.com

1.4 Emergency telephone number:

Anti poisoning centre:

ITALY (Rome): 06/305 43 43
ITALY (Milan): 02/66 10 10 29

SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48
FRANCE (Toulouse): 05 61 77 74 47
FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance.

In accordance with Regulation (EU) No 1272/2008:

Met. Corr. 1 : May be corrosive to metals.

Skin Corr. 1A : Causes severe skin burns and eye damage.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



Astral pH Minus Liquid

Version: 1

Revision date: 11/01/2017

Page 2 of 9

Print date: 11/01/2017

Danger

H statements:

- | | |
|------|--|
| H290 | May be corrosive to metals. |
| H314 | Causes severe skin burns and eye damage. |

P statements:

- | | |
|------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P260 | Do not breathe vapours. |
| P264 | Wash hands thoroughly after handling. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P501 | Dispose of contents/container in accordance with applicable regulations. |

Contains:

sulphuric acid

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Chemical Name:	[1] sulphuric acid
Index No:	016-020-00-8
CAS No:	7664-93-9
CE No:	231-639-5
Registration No:	01-2119458838-20-XXXX

[1] Substance with a Community workplace exposure limit (see section 8.1).

3.2 Mixtures.

Not Applicable.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

Astral pH Minus Liquid

Version: 1

Revision date: 11/01/2017



Page 3 of 9

Print date: 11/01/2017

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the substance.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

None in particular.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

Astral pH Minus Liquid

Version: 1

Revision date: 11/01/2017

Page 4 of 9

Print date: 11/01/2017

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³	
sulphuric acid	7664-93-9	European Union [1]	Eight hours		0,05	
			Short term			
		United Kingdom [2]	Eight hours	0,05		The mist is defined as the thoracic fraction
			Short term			

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
sulphuric acid N. CAS: 7664-93-9 N. CE: 231-639-5	DNEL (Workers)	Inhalation, Long-term, Local effects	0,05 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	pH regulator		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Non-disposable protective gloves against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.		
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



Astral pH Minus Liquid

Version: 1

Revision date: 11/01/2017

Page 5 of 9

Print date: 11/01/2017

Skin protection:		
PPE:	Chemical protective clothing	
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.	
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.	
PPE:	Anti-static safety footwear against chemicals.	
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.	
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345	
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.	
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: Colourless

Odour: Characteristic

Odour threshold: N.A./N.A.

pH: 0 - 1 (10%)

Melting point: N.A./N.A.

Boiling Point: 315 - 338 °C

Flash point: N.A./N.A.

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: 1.29 - 1.33 (20 °C) g/cm³

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: 100 %

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: No applicable

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

Astral pH Minus Liquid



Version: 1
Revision date: 11/01/2017

Page 6 of 9
Print date: 11/01/2017

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information.

Name	Acute toxicity			
	Type	Test	Kind	Value
sulphuric acid CAS No: 7664-93-9 EC No: 231-639-5	Oral	LD50 [1] Hoechst AG (1985): 85.0427)	Rat	5000 mg/kg bw [1] Unveroffentl. Unters. (Ber.-Nr 85.0427)
	Dermal			
	Inhalation			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin Corrosive, Category 1A: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

Astral pH Minus Liquid

Version: 1
Revision date: 11/01/2017



Page 7 of 9
Print date: 11/01/2017

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
sulphuric acid CAS No: 7664-93-9 EC No: 231-639-5	Fish	LC50	Gambusia affinis	42 mg/L (96 h) [1]
		[1] Wallen et al. (1957), Sewage and Industrial Wastes 29 (6) 695-711		
	Aquatic invertebrates	EC50	Daphnia magna	29 mg/L (24 h) [1]
		[1] IRCHA et Ministère de l'Environnement et du Cadre de Vie, Les produits chimiques dans l'environnement (1981)		
Aquatic plants				

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation.

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

Astral pH Minus Liquid

Version: 1

Revision date: 11/01/2017

Page 8 of 9

Print date: 11/01/2017

14.1 UN number.

UN No: UN2796

14.2 UN proper shipping name.

Description:

ADR: UN 2796, SULPHURIC ACID, 8, PG II, (E)

IMDG: UN 2796, SULPHURIC ACID, 8, PG II

ICAO: UN 2796, SULPHURIC ACID, 8, PG II

14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 8



Hazard number: 80

ADR LQ: 1 L

IMDG LQ: 1 L

ICAO LQ: 0,5 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

Proceed in accordance with point 6.

IMDG Code segregation group: 1 Acids

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

Classification codes:

Met. Corr. 1 : Corrosive to metals, Category 1

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



Astral pH Minus Liquid

Version: 1

Revision date: 11/01/2017

Page 9 of 9

Print date: 11/01/2017

Skin Corr. 1A : Skin Corrosive, Category 1A

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
7664-93-9	sulphuric acid	Registered

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.